


EC type examination certificate

EG-Baumusterprüfbescheinigung

CE-0085CP0237Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Pressure Equipment Directive (97/23/EC) <i>EG-Druckgeräterichtlinie (97/23/EG)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	GASCAT Indústria e Comércio Ltda Rodovia SP 73, 1141, Bairro Pimenta, BR- 13347-390 Indaiatuba/SP
Distributor <i>Vertreiber</i>	GASCAT Indústria e Comércio Ltda Rodovia SP 73, 1141, Bairro Pimenta, BR- 13347-390 Indaiatuba/SP
Product Category <i>Produktart</i>	gas fittings: Pressure regulator for natural gas and all-gas (4301)
Product Description <i>Produktbezeichnung</i>	pressure regulator
Model <i>Modell</i>	Brise ...
Test Reports <i>Prüfberichte</i>	type testing: 14/126/4303/961 from 24.10.2014 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/97/23/EG A III B (29.05.1997)

Date of Expiry / File No. 23.07.2024 / 14-0062-GDE
Ablaufdatum / Aktenzeichen

11.11.2014 Kö A-1/2 
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to EN 45011:1998 and notified by the government of the Federal Republic of Germany for certification of pressure equipment under EC Directive 97/23/EC.

DVGW CERT GmbH ist von der DAkkS nach DIN EN 45011:1998 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Druckgeräten und Baugruppen gemäß Richtlinie 97/23/EG.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
Brise	nominal diameter: 1" max. allowable pressure PS: 10 bar	
Brise	nominal diameter: 2" max. allowable pressure PS: 10 bar	
Brise	nominal diameter: 3" max. allowable pressure PS: 10 bar	

Type Variation Ausführungsvariante	Explanations Erläuterungen
Brise	pressure regulator, pressure range: 20 to 1500 mbar
Brise N	pressure regulator with SSV, pressure range: 20 to 1500 mbar, shut Off range (OVER pressure): 45 to 2000 mbar, (UNDER pressure): 60 bis 330 mbar
Brise Plus	pressure regulator with pilot, pressure range: 7,5 to 2400 mbar
Brise Plus N	pressure regulator with pilot and SSV, pressure range: 7,5 to 2400 mbar, shut Off range (OVER pressure): 45 to 2000 mbar, (UNDER pressure): 60 bis 330 mbar

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Connections: flanges: ANSI B16.5 or DIN PN 16
body material: ductile iron GGG40
medium: burning gases and non aggressive gases
temperature range: -20°C up to +60°C