

EU type examination certificate
EU-Baumusterprüfbescheinigung

CE-0085CP0240
 Product Identification No.
 Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Pressure Equipment Directive (2014/68/EU) <i>EU-Druckgeräterichtlinie (2014/68/EU)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	GASCAT Indústria e Comércio Ltda Rodovia SP 73, 1141, Bairro Pimenta, BR- 13347-390 Indaiatuba/SP
Distributor <i>Vertreiber</i>	GASCAT Indústria e Comércio Ltda Rodovia SP 73, 1141, Bairro Pimenta, BR- 13347-390 Indaiatuba/SP
Product Category <i>Produktart</i>	Gas fittings: Pressure regulator for natural gas and all-gas (4301)
Product description <i>Produktbezeichnung</i>	spring operated regulator for the residential and commercial field
Model <i>Modell</i>	Ares-N
Test Reports <i>Prüfberichte</i>	Laboratory control test: 21-01482-KP03 from 01.11.2023 (EBI)
Test Basis <i>Prüfgrundlagen</i>	2014/68/EU A III B Baumusterprüfung (15.04.2014)



Date of Expiry / File No. 23.07.2025 / 24-0317-GDV
Ablaufdatum / Aktenzeichen

15.07.2024 Ca A-1/2

JA. W. ZL

Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH – notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of pressure equipment

DVGW CERT GmbH – von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Druckgeräten

DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
Ares-N	Outlet pressure: 5 ... 240 mbar Nominal diameter: DN 3/4" Max. allowable pressure PS: 10 bar	
Ares-N	Outlet pressure: 5 ... 240 mbar Nominal diameter: 1" Max. allowable pressure PS: 10 bar	

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

Connections: thread: NPT, BSP, flanges: ANSI
body material: ductile iron GGG40, carbon steel ASTM A216 Gr WCB
medium: burning gases and non aggressive gases
temperature range: -20°C up to +60°C
can be combined with SSV type G-10

